

Linear

Bet DL1482

Linear luminaire



Linear luminaire. 13 W. 24° or 36° beam. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø221 mm
- LED source: Citizen

Power 13 W	Voltage max 36 V	Luminous flux 1180 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 24°, 36°
IP rating IP20	Certifications CE	Mounting Recessed
Finishes Black		


Models

Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1482	13 W	max 36 V	1180 lm	97 CRI	L225 x W28 x H29 mm	Ø221 mm	24° 36°	350 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1482, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1482, 13 W, 24° beam



Luminous flux	1,180 lm
Efficacy	91 lm/W
Peak intensity	5,998 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	225 × 28 × 29 mm
Data	Calculated from catalogue data

DL1482, 13 W, 36° beam



Luminous flux	1,180 lm
Efficacy	91 lm/W
Peak intensity	2,701 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	225 × 28 × 29 mm
Data	Calculated from catalogue data