

Recessed

Bet DL1930

Recessed spotlight




Recessed spotlight. 15 W. 24° or 36° beam. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø135 mm
- LED source: Citizen

Power 15 W	Voltage max 30 V	Luminous flux 960 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 24°, 36°
IP rating IP20	Certifications CE	Mounting Recessed
Finishes Black		

Dimensions




Models

Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1930	15 W	max 30 V	960 lm	97 CRI	L143 x W68 x H55 mm	Ø135 mm	24° 36°	500 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1930, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1930, 15 W, 24° beam



Luminous flux	960 lm
Efficacy	64 lm/W
Peak intensity	4,880 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	143 × 68 × 55 mm
Data	Calculated from catalogue data

DL1930, 15 W, 36° beam



Luminous flux	960 lm
Efficacy	64 lm/W
Peak intensity	2,198 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	143 × 68 × 55 mm
Data	Calculated from catalogue data