

Surface

C3-4215

Surface luminaire




Surface luminaire. 30 W. 15° or 60° beam. 3000, 4000 K. 97 CRI.

— LED source: Citizen

Power 30 W	Luminous flux 3100–3200 lm	Colour temperature 3000 K, 4000 K
CRI 97 CRI	Beam angles 15°, 60°	IP rating IP20
Certifications CE, RoHS, EMC, LVD	Mounting Surface	Control DALI, 0-10V, Triac, Casambi

Finishes
White, Black, Grey

Dimensions



Models

Code	Power	Flux	CRI	Size	Beam
C3-4215	30 W	3100–3200 lm	97 CRI	85 × 225 mm	15° 60°


Finishes



Photometric data

Illuminance on the beam axis (lx) and beam diameter at each mounting distance, per model and beam angle. IES files for every model and beam can be downloaded from the product page.


30 W



Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for C3-4215, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

C3-4215, 30 W, 15° beam



Luminous flux	1,099 lm
Efficacy	37 lm/W
Peak intensity	14,215 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	225 × 85 mm
Data	Calculated from catalogue data

C3-4215, 30 W, 60° beam



Luminous flux	4,408 lm
Efficacy	147 lm/W
Peak intensity	3,792 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Size	225 × 85 mm
Data	Calculated from catalogue data