

Recessed

D3-4091

Recessed spotlight




Recessed spotlight. 24 W. Four beam angles, 15° to 55°. 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø90 mm
- LED source: Citizen

Power 24 W	Luminous flux 1900–2100 lm	Colour temperature 3000 K, 4000 K
CRI 97 CRI	Beam angles 15°, 24°, 36°, 55°	IP rating IP20
Certifications CE, RoHS, EMC, LVD	Mounting Recessed	Control DALI, 0-10V, Triac, Casambi
Finishes White, Black, Grey		

Dimensions



Models

Code	Power	Flux	CRI	Size	Cut-out	Beam
D3-4091	24 W	1900–2100 lm	97 CRI	Ø120 × 113 mm	Ø90 mm	15° 24° 36° 55°

Photometric data

Illuminance on the beam axis (lx) and beam diameter at each mounting distance, per model and beam angle. IES files for every model and beam can be downloaded from the product page.


24 W

15°			24°			36°		
Ø0.33 m	11,922 lx	1 m	Ø0.46 m	8,683 lx	1 m	Ø0.68 m	4,609 lx	1 m
Ø0.66 m	2,980 lx	2 m	Ø0.92 m	2,170 lx	2 m	Ø1.36 m	1,150 lx	2 m
Ø0.99 m	1,324 lx	3 m	Ø1.38 m	964 lx	3 m	Ø2.04 m	512 lx	3 m
Beam	1 m		2 m			3 m		
15°	11,922 lx Ø330 mm		2,980 lx Ø660 mm			1,324 lx Ø990 mm		
24°	8,683 lx Ø460 mm		2,170 lx Ø920 mm			964 lx Ø1380 mm		
36°	4,609 lx Ø680 mm		1,150 lx Ø1360 mm			512 lx Ø2040 mm		

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for D3-4091, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

D3-4091, 24 W, 15° beam




Luminous flux	922 lm
Efficacy	38 lm/W
Peak intensity	11,920 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø120 × 113 mm
Data	Calculated from catalogue data

D3-4091, 24 W, 24° beam




Luminous flux	1,708 lm
Efficacy	71 lm/W
Peak intensity	8,680 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø120 × 113 mm
Data	Calculated from catalogue data

D3-4091, 24 W, 36° beam



Luminous flux	2,013 lm
Efficacy	84 lm/W
Peak intensity	4,608 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø120 × 113 mm
Data	Calculated from catalogue data

D3-4091, 24 W, 55° beam



Luminous flux	1,900 lm
Efficacy	79 lm/W
Peak intensity	1,924 cd, 1,012 cd/klm
Beam angle (50%)	55°
Field angle (10%)	100.2°
Cut-off angle (2.5%)	63°
Flux 0-30° / 30-60° / 60-90°	58.2 / 38.8 / 3 %
Size	Ø120 × 113 mm
Data	Calculated from catalogue data