

Recessed

D3-4315

Recessed spotlight




Recessed spotlight. 6 W. Four beam angles, 15° to 50°. 3000, 4000 K. IP44. 97 CRI.

- Ceiling cut-out Ø55 mm
- LED source: Citizen

Power 6 W	Luminous flux 500–600 lm	Colour temperature 3000 K, 4000 K
CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°	IP rating IP44
Certifications CE, RoHS, EMC, LVD	Mounting Recessed	Control DALI, 0-10V, Triac, Casambi
Finishes Black		

Dimensions




Models

Code	Power	Flux	CRI	Size	Cut-out	Beam
D3-4315	6 W	500–600 lm	97 CRI	Ø63 x H59 mm	Ø55 mm	15° 24° 36° 50°

Photometric data

Illuminance on the beam axis (lx) and beam diameter at each mounting distance, per model and beam angle. IES files for every model and beam can be downloaded from the product page.

6 W




Beam	1 m	2 m	3 m
36°	1,168 lx Ø740 mm	292 lx Ø1470 mm	129 lx Ø2210 mm

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for D3-4315, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

D3-4315, 6 W, 36° beam




Luminous flux	510 lm
Efficacy	85 lm/W
Peak intensity	1,168 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø63 × 59 mm
Data	Calculated from catalogue data

D3-4315, 6 W, 15° beam




Luminous flux	500 lm
Efficacy	83 lm/W
Peak intensity	6,465 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø63 × 59 mm
Data	Calculated from catalogue data

D3-4315, 6 W, 24° beam



Luminous flux	500 lm
Efficacy	83 lm/W
Peak intensity	2,542 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø63 × 59 mm
Data	Calculated from catalogue data

D3-4315, 6 W, 50° beam



Luminous flux	500 lm
Efficacy	83 lm/W
Peak intensity	607 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0–30° / 30–60° / 60–90°	64.8 / 33.6 / 1.5 %
Size	Ø63 × 59 mm
Data	Calculated from catalogue data