

Outdoor

Deck DL1332

Outdoor luminaire




Outdoor luminaire.

- Ceiling cut-out Ø34 mm
- LED source: Citizen

Voltage max 3 V, 24 V DC	Luminous flux 90 lm	Colour temperature 2700 K, 3000 K, 4000 K
CRI 97 CRI	Beam angles 15°, 24°, 36°, 60°	IP rating IP67
Certifications CE	Mounting Floor, Recessed, Wall	Finishes Black

Dimensions




Models

Code	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1332	max 3 V, 24 V DC	90 lm	97 CRI	$\varnothing 37 \times 53\text{ mm}$	$\varnothing 34\text{ mm}$	15° 24° 36° 60°	350 / 700 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1332, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1332, 15° beam




Luminous flux	90 lm
Peak intensity	1,164 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø37 × 53 mm
Data	Calculated from catalogue data

DL1332, 24° beam




Luminous flux	90 lm
Peak intensity	457 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø37 × 53 mm
Data	Calculated from catalogue data

DL1332, 36° beam



Luminous flux	90 lm
Peak intensity	206 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø37 × 53 mm
Data	Calculated from catalogue data

DL1332, 60° beam



DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.