

Recessed

Eco DL0623

Recessed spotlight



Recessed spotlight. 13, 20 or 26 W. 100° beam. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø125 / Ø160 / Ø200 mm
- LED source: Citizen

Power	Voltage	Luminous flux
13 W, 20 W, 26 W	max 37 V, max 28 V	1241 lm, 1830 lm, 2579 lm
Colour temperature	CRI	Beam angles
2700 K, 3000 K, 4000 K	97 CRI	100°
IP rating	Certifications	Mounting
IP20	CE	Recessed
Finishes		
Black		

Dimensions



Models

Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL0623	13 W	max 37 V	1241 lm	97 CRI	Ø140 × 49 mm	Ø125 mm	100°	350 mA
DL0624	20 W	max 28 V	1830 lm	97 CRI	Ø182 × 57 mm	Ø160 mm	100°	700 mA
DL0625	26 W	max 37 V	2579 lm	97 CRI	Ø230 × 62 mm	Ø200 mm	100°	700 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL0625, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL0625, 26 W, 100° beam

