

Surface

F5-2G

Surface luminaire




Surface luminaire. 12 W. Three beam angles, 15° to 36°. 3000, 4000 K. 97 CRI.

- LED source: Citizen
- UGR <17 (15°), <18 (24°), <22 (36°)

Power 12 W	Voltage 36 V	Colour temperature 3000 K, 4000 K
CRI 97 CRI	Beam angles 15°, 24°, 36°	IP rating IP20
Mounting Surface	Control On/Off	Finishes White, Black, Silver, Brass, Bronze


Dimensions



Models

Code	Power	Voltage	CRI	Size	Beam	Notes
SU-F5-1201-2G	12 W	36 V	97 CRI	Ø85 × 73 mm	15° 24° 36°	300 mA


Finishes



Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for SU-F5-1201-2G, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

SU-F5-1201-2G, 12 W, 15° beam




Luminous flux	900 lm
Efficacy	75 lm/W
Peak intensity	11,637 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø85 × 73 mm
Data	Estimated from catalogue data

SU-F5-1201-2G, 12 W, 24° beam



Luminous flux	900 lm
Efficacy	75 lm/W
Peak intensity	4,575 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø85 × 73 mm
Data	Estimated from catalogue data

SU-F5-1201-2G, 12 W, 36° beam



Luminous flux	900 lm
Efficacy	75 lm/W
Peak intensity	2,060 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø85 × 73 mm
Data	Estimated from catalogue data

