Recessed

Fort DL1500

Recessed spotlight

Recessed spotlight. 7 or 10 W. Four beam angles, 15° to 55°. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø150 mm
- LED source: Citizen

Power **7 W, 10 W**	Voltage **2 × max 19 V**	Luminous flux **2 × 630 lm, 2 × 960 lm**
Colour temperature **2700 K, 3000 K, 4000 K**	CRI **97 CRI**	Beam angles **15°, 24°, 36°, 55°**
IP rating **IP20**	Certifications **CE**	Mounting **Recessed**
Finishes **White**		

Dimensions



Models

Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1500	7 W	2 × max 19 V	2 × 630 lm	97 CRI	156 × 86 x H100 mm	Ø150 mm	15° 24° 36° 55°	350 mA
DL1500	10 W	2 × max 19 V	2 × 960 lm	97 CRI	156 × 86 x H100 mm	Ø150 mm	15° 24° 36° 55°	500 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1500, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1500, 10 W, 15° beam





Luminous flux	1,920 lm
Efficacy	192 lm/W
Peak intensity	24,825 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	156 × 86 × 100 mm
Data	Calculated from catalogue data

DL1500, 10 W, 24° beam





Luminous flux	1,920 lm
Efficacy	192 lm/W
Peak intensity	9,760 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	156 × 86 × 100 mm
Data	Calculated from catalogue data

DL1500, 10 W, 36° beam





Luminous flux	1,920 lm
Efficacy	192 lm/W
Peak intensity	4,395 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	156 × 86 × 100 mm
Data	Calculated from catalogue data

DL1500, 10 W, 55° beam





Luminous flux	1,920 lm
Efficacy	192 lm/W
Peak intensity	1,944 cd, 1,012 cd/klm
Beam angle (50%)	55°
Field angle (10%)	100.2°
Cut-off angle (2.5%)	63°
Flux 0–30° / 30–60° / 60–90°	58.2 / 38.8 / 3 %
Size	156 × 86 × 100 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.