

Recessed

Global-15B

Recessed spotlight



Recessed spotlight. 15 W. Three beam angles, 24° to 60°. 3000, 4000 K. 97 CRI.

- LED source: Citizen
- UGR <9 (15°), <9 (24°), <14 (36°), <19 (50°)

Power 15 W	Voltage 36 V	Colour temperature 3000 K, 4000 K
CRI 97 CRI	Beam angles 24°, 36°, 60°	IP rating IP20
Mounting Recessed	Control On/Off, Triac	Finishes White, Black, Silver, Brass, Bronze


Models

Code	Version	Power	Voltage	CRI	Beam	Notes
Global-15B	Module IP20	15 W	36 V	97 CRI	24° 36° 60°	350 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for Global-15B, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

Global-15B, 15 W, 24° beam




Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	5,719 cd, 5,083 cd/k1m
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Data	Estimated from catalogue data

Global-15B, 15 W, 36° beam



Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	2,575 cd, 2,289 cd/k1m
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Data	Estimated from catalogue data

Global-15B, 15 W, 60° beam



Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	968 cd, 860 cd/k1m
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Data	Estimated from catalogue data

