

Recessed

Grill DL1309

Recessed spotlight




Recessed spotlight. 7 W. Four beam angles, 15° to 55°. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø56 mm
- LED source: Citizen

Power 7 W	Voltage max 19 V	Luminous flux 630 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 55°
IP rating IP20	Certifications CE	Mounting Recessed
Finishes White		

Dimensions




Models

Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1309	7 W	max 19 V	630 lm	97 CRI	Ø60 × 72 mm	Ø56 mm	15° 24° 36° 55°	350 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1309, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1309, 7 W, 15° beam




Luminous flux	630 lm
Efficacy	90 lm/W
Peak intensity	8,146 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø60 × 72 mm
Data	Calculated from catalogue data

DL1309, 7 W, 24° beam




Luminous flux	630 lm
Efficacy	90 lm/W
Peak intensity	3,202 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø60 × 72 mm
Data	Calculated from catalogue data

DL1309, 7 W, 36° beam



Luminous flux	630 lm
Efficacy	90 lm/W
Peak intensity	1,442 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø60 × 72 mm
Data	Calculated from catalogue data

DL1309, 7 W, 55° beam



Luminous flux	630 lm
Efficacy	90 lm/W
Peak intensity	638 cd, 1,012 cd/klm
Beam angle (50%)	55°
Field angle (10%)	100.2°
Cut-off angle (2.5%)	63°
Flux 0-30° / 30-60° / 60-90°	58.2 / 38.8 / 3 %
Size	Ø60 × 72 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.