

Moon system

M-P03+B50

Moon spotlight




Spotlight for the Moon magnetic track. 6 W. Four beam angles, 15° to 60°. 2700, 3000, 4000 K. 97 CRI.

— LED source: Citizen

Power 6 W	Voltage 48 V DC	Colour temperature 2700 K, 3000 K, 4000 K
CRI 97 CRI	Beam angles 15°, 24°, 36°, 60°	IP rating IP20
Mounting Magnetic track	Control On/Off, Triac	Finishes White, Black, Silver, Brass, Bronze

Dimensions


M-P03+B50



Models

Code	Version	Power	Voltage	CRI	Size	Beam	Notes
M-P03+B50	B50	6 W	48 V DC	97 CRI	Ø50 × 40 mm; adapter 152 mm	15° 24° 36° 60°	LED 36 V, 150 mA


Finishes



Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for M-P03+B50, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

M-P03+B50, 6 W, 15° beam




Luminous flux	450 lm
Efficacy	75 lm/W
Peak intensity	5,818 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø50 × 40 mm
Data	Estimated from catalogue data

M-P03+B50, 6 W, 24° beam




Luminous flux	450 lm
Efficacy	75 lm/W
Peak intensity	2,287 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø50 × 40 mm
Data	Estimated from catalogue data

M-P03+B50, 6 W, 36° beam



Luminous flux	450 lm
Efficacy	75 lm/W
Peak intensity	1,030 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø50 × 40 mm
Data	Estimated from catalogue data

M-P03+B50, 6 W, 60° beam



Luminous flux	450 lm
Efficacy	75 lm/W
Peak intensity	387 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Size	Ø50 × 40 mm
Data	Estimated from catalogue data