

Slim 15 mm system

Locus Spot TW10


Slim 15 mm spotlight



Spotlight for the Slim 15 mm magnetic track. 10 W. 24° or 36° beam. 3000, 4000, 5000 K. 97 CRI. — LED source: Citizen

Power 10 W	Voltage 48 V DC	Colour temperature 3000 K, 4000 K, 5000 K
CRI 97 CRI	Beam angles 24°, 36°	Mounting Magnetic track
Control Casambi, Tuya, DALI, 0-10V	Finishes White, Black, Silver, Nickel, Gold	

Dimensions



Models

Code	Power	Voltage	CRI	Size	Beam
M15-TW10	10 W	48 V DC	97 CRI	Ø80 × 35 × 100 mm	24° 36°

Finishes



Gold



Nickel



Black




White

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for M15-TW10, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

M15-TW10, 10 W, 24° beam



Luminous flux	750 lm
Efficacy	75 lm/W
Peak intensity	3,812 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø80 × 35 mm
Data	Estimated from catalogue data

M15-TW10, 10 W, 36° beam



Luminous flux	750 lm
Efficacy	75 lm/W
Peak intensity	1,717 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø80 × 35 mm
Data	Estimated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.