

Surface

SU-M7-3



Surface luminaire



Surface luminaire. 12 W. Four beam angles, 15° to 60°. — LED source: Citizen
2700, 3000, 4000 K. 97 CRI.

Power 12 W	Voltage 36 V	Colour temperature 2700 K, 3000 K, 4000 K
CRI 97 CRI	Beam angles 15°, 24°, 36°, 60°	IP rating IP20
Mounting Surface	Control On/Off	Finishes Black

Dimensions




Models

Code	Power	Voltage	CRI	Size	Beam	Notes
SU-M7-3	12 W	36 V	97 CRI	Ø75 × 105 mm	15° 24° 36° 60°	300 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for SU-M7-3, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

SU-M7-3, 12 W, 15° beam




Luminous flux	900 lm
Efficacy	75 lm/W
Peak intensity	11,637 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø75 × 105 mm
Data	Estimated from catalogue data

SU-M7-3, 12 W, 24° beam




Luminous flux	900 lm
Efficacy	75 lm/W
Peak intensity	4,575 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø75 × 105 mm
Data	Estimated from catalogue data

SU-M7-3, 12 W, 36° beam



Luminous flux	900 lm
Efficacy	75 lm/W
Peak intensity	2,060 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø75 × 105 mm
Data	Estimated from catalogue data

SU-M7-3, 12 W, 60° beam



Luminous flux	900 lm
Efficacy	75 lm/W
Peak intensity	774 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Size	Ø75 × 105 mm
Data	Estimated from catalogue data