

Recessed

Mars-1203

Recessed spotlight




Recessed spotlight. 12 W. 24° or 36° beam. 2700, 3000, 4000 K. IP44. 97 CRI.

- Ceiling cut-out Ø55 mm
- LED source: Citizen
- UGR <10 (15°), <13 (24°), <16 (36°), <20 (50°)

Power 12 W	Voltage 36 V	Colour temperature 2700 K, 3000 K, 4000 K
CRI 97 CRI	Beam angles 24°, 36°	IP rating IP44
Mounting Recessed	Control On/Off	Finishes White, Black, Silver, Brass, Bronze, Gun black

Dimensions




Models

Code	Power	Voltage	CRI	Size	Cut-out	Beam	Notes
Mars-1203	12 W	36 V	97 CRI	Ø62 × 59 mm	Ø55 mm	24° 36°	300 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for Mars-1203, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

Mars-1203, 12 W, 24° beam



Luminous flux	900 lm
Efficacy	75 lm/W
Peak intensity	4,575 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø62 × 59 mm
Data	Estimated from catalogue data

Mars-1203, 12 W, 36° beam



Luminous flux	900 lm
Efficacy	75 lm/W
Peak intensity	2,060 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø62 × 59 mm
Data	Estimated from catalogue data

DiaNoche
Via Tortona, 31, 20144 Milano MI, Italy
service@dianoche.it
dianoche.it

Technical data may change without notice.