

Recessed

Maxi DL1725

Recessed spotlight




Recessed spotlight. 5 W. Four beam angles, 15° to 50°. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø35 mm
- LED source: Citizen

Power 5 W	Luminous flux 400 lm	Colour temperature 2700 K, 3000 K, 4000 K
CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°	IP rating IP20
Certifications CE	Mounting Recessed	Finishes Black

Dimensions




Models

Code	Power	Flux	CRI	Size	Cut-out	Beam	Notes
DL1725	5 W	400 lm	97 CRI	Ø40 x H65 mm	Ø35 mm	15° 24° 36° 50°	250 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1725, from the same data as the IES and LDT files on the product page. Curves marked measured come from goniophotometer tests in the laboratory; the others are calculated from catalogue data, not measured.

DL1725, 4.6 W, 3000 K, 53° beam, measured




Luminous flux	153 lm
Efficacy	33 lm/W
Peak intensity	165 cd, 1,078 cd/klm
Beam angle (50%)	53°
Field angle (10%)	98°
Cut-off angle (2.5%)	77°
Flux 0–30° / 30–60° / 60–90°	57.9 / 38.4 / 3.7 %
Size	Ø40 × 65 mm
Data	Measured with a goniophotometer (EVERFINE GO-2000B), 19 August 2025

DL1725, 5 W, 15° beam




Luminous flux	400 lm
Efficacy	80 lm/W
Peak intensity	5,172 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø40 × 65 mm
Data	Calculated from catalogue data

DL1725, 5 W, 24° beam




Luminous flux	400 lm
Efficacy	80 lm/W
Peak intensity	2,033 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø40 × 65 mm
Data	Calculated from catalogue data

DL1725, 5 W, 36° beam



Luminous flux	400 lm
Efficacy	80 lm/W
Peak intensity	916 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø40 × 65 mm
Data	Calculated from catalogue data

DL1725, 5 W, 50° beam



Luminous flux	400 lm
Efficacy	80 lm/W
Peak intensity	485 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0–30° / 30–60° / 60–90°	64.8 / 33.6 / 1.5 %
Size	Ø40 × 65 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.