

Recessed

Moon DL1191

Recessed spotlight




Recessed spotlight.

- Ceiling cut-out Ø83 mm
- LED source: Citizen

Voltage max 19 V	Luminous flux 630 / 960 lm	Colour temperature 2700 K, 3000 K, 4000 K
CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°	IP rating IP54
Certifications CE	Mounting Recessed	Finishes White

Dimensions




Models

Code	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1191	max 19 V	630 / 960 lm	97 CRI	Ø91 × 110 mm	Ø83 mm	15° 24° 36° 50°	350 / 500 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1191, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1191, 15° beam




Luminous flux	630 lm
Peak intensity	8,146 cd, 12,930 cd/k1m
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø91 × 110 mm
Data	Calculated from catalogue data

DL1191, 24° beam




Luminous flux	630 lm
Peak intensity	3,202 cd, 5,083 cd/k1m
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø91 × 110 mm
Data	Calculated from catalogue data

DL1191, 36° beam



Luminous flux	630 lm
Peak intensity	1,442 cd, 2,289 cd/k1m
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø91 × 110 mm
Data	Calculated from catalogue data

DL1191, 50° beam



DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.