

Linear

OL-KNNF24064T09-8A39

Linear luminaire




Linear luminaire. 4.8 W. 2700, 3000, 4000, 6500 K.
IP20/54/66/67. 97 CRI.

— LED source: Citizen

Power 4.8 W	Voltage 24 V	Luminous flux 552 lm/m, 566 lm/m, 600 lm/m
Colour temperature 2700 K, 3000 K, 4000 K, 6500 K	CRI 97 CRI	IP rating IP20/54/66/67
Certifications CE, RoHS, UL, ErP	Mounting Recessed	Finishes Black

Dimensions




Models

Code	Version	Power	Voltage	Flux	CRI	Size
OL - KNNF24064T09 - 8A39	2700 K	4.8 W	24 V	552 lm/m	97 CRI	PCB W8 mm x T1.1 mm
OL - INNF24064T09 - 8A39	3000 K	4.8 W	24 V	566 lm/m	97 CRI	PCB W8 mm x T1.1 mm
OL - DNNF24064T09 - 8A39	4000 K	4.8 W	24 V	600 lm/m	97 CRI	PCB W8 mm x T1.1 mm
OL - WNNF24064T09 - 8A39	6500 K	4.8 W	24 V	600 lm/m	97 CRI	PCB W8 mm x T1.1 mm

Photometric data

Illuminance on the beam axis (lx) and beam diameter at each mounting distance, per model and beam angle. IES files for every model and beam can be downloaded from the product page.


4.8 W



Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for OL-KNNF24064T09-8A39, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

OL-KNNF24064T09-8A39, 4.8 W, 116.4° beam



Luminous flux	736 lm
Efficacy	153 lm/W
Peak intensity	227 cd, 308 cd/klm
Beam angle (50%)	116.4°
Cut-off angle (2.5%)	90°
Flux 0–30° / 30–60° / 60–90°	23.7 / 45.5 / 30.8 %
Size	8 × 0 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.