

Wall

Oval Indoor WL0041


Wall light



Wall light. 3 W. 24° or 36° beam. 2700, 3000, 4000 K. 97 CRI. — LED source: Citizen

Power 3 W	Voltage 230 V AC	Luminous flux 160 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 24°, 36°
IP rating IP20	Certifications CE	Mounting Surface, Wall

Dimensions




Models

Code	Power	Voltage	Flux	CRI	Size	Beam
WL0041	3 W	230 V AC	160 lm	97 CRI	160, 121, 76, 365, Ø26, 90 mm	24° 36°

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for WL0041, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

WL0041, 3 W, 24° beam



Luminous flux	160 lm
Efficacy	53 lm/W
Peak intensity	813 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø26 × 160 mm
Data	Calculated from catalogue data

WL0041, 3 W, 36° beam



Luminous flux	160 lm
Efficacy	53 lm/W
Peak intensity	366 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø26 × 160 mm
Data	Calculated from catalogue data