Wall

Oval Indoor WL0048

Wall light

Wall light. 3 W. Three beam angles, 20° to 60°. 2700, 3000, 4000 K. 97 CRI.

- LED source: Citizen

Power **3 W**	Voltage **230 V AC**	Luminous flux **160 lm**
Colour temperature **2700 K, 3000 K, 4000 K**	CRI **97 CRI**	Beam angles **20°, 40°, 60°**
IP rating **IP20**	Certifications **CE**	Mounting **Surface, Wall**

Dimensions



Models

Code	Power	Voltage	Flux	CRI	Size	Beam
WL0048	3 W	230 V AC	160 lm	97 CRI	135, 110, 26, 26, 50, 30 mm	20° 40° 60°

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for WL0048, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

WL0048, 3 W, 20° beam





Luminous flux	160 lm
Efficacy	53 lm/W
Peak intensity	1,167 cd, 7,296 cd/klm
Beam angle (50%)	20°
Field angle (10%)	36.5°
Cut-off angle (2.5%)	23°
Flux 0–30° / 30–60° / 60–90°	99.8 / 0.2 / 0 %
Size	135 × 110 × 26 mm
Data	Calculated from catalogue data

WL0048, 3 W, 40° beam





Luminous flux	160 lm
Efficacy	53 lm/W
Peak intensity	298 cd, 1,864 cd/klm
Beam angle (50%)	40°
Field angle (10%)	72.9°
Cut-off angle (2.5%)	46°
Flux 0–30° / 30–60° / 60–90°	79.9 / 19.9 / 0.2 %
Size	135 × 110 × 26 mm
Data	Calculated from catalogue data

WL0048, 3 W, 60° beam





Luminous flux	160 lm
Efficacy	53 lm/W
Peak intensity	138 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Size	135 × 110 × 26 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.