

Wall

Oval Indoor WL0103

Wall light




Wall light. 8 W. Four beam angles, 15° to 50°. 2700, 3000, 4000 K. 97 CRI.

— LED source: Citizen

Power 8 W	Voltage 230 V AC	Luminous flux 400 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°
IP rating IP20	Certifications CE	Mounting Surface, Wall
Finishes Black		

Dimensions




Models

Code	Power	Voltage	Flux	CRI	Size	Beam
WL0103	8 W	230 V AC	400 lm	97 CRI	287, 135, 70, Ø90, 32, 50, 199 mm	15° 24° 36° 50°

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for WL0103, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

WL0103, 8 W, 15° beam




Luminous flux	400 lm
Efficacy	50 lm/W
Peak intensity	5,172 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø90 × 287 mm
Data	Calculated from catalogue data

WL0103, 8 W, 24° beam




Luminous flux	400 lm
Efficacy	50 lm/W
Peak intensity	2,033 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø90 × 287 mm
Data	Calculated from catalogue data

WL0103, 8 W, 36° beam



Luminous flux	400 lm
Efficacy	50 lm/W
Peak intensity	916 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø90 × 287 mm
Data	Calculated from catalogue data

WL0103, 8 W, 50° beam



Luminous flux	400 lm
Efficacy	50 lm/W
Peak intensity	485 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0–30° / 30–60° / 60–90°	64.8 / 33.6 / 1.5 %
Size	Ø90 × 287 mm
Data	Calculated from catalogue data