

Suspended

Pro PH0078

Pendant



Pendant. 19, 27 or 35 W. 50° beam. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø76 mm
- LED source: Citizen

Power	Voltage	Luminous flux
19 W, 27 W, 35 W	24 V DC	1440 lm, 2160 lm, 2880 lm
Colour temperature	CRI	Beam angles
2700 K, 3000 K, 4000 K	97 CRI	50°
IP rating	Certifications	Mounting
IP20	CE	Suspended
Finishes		
White		

Models

Code	Version	Power	Voltage	Flux	CRI	Size	Cut-out	Beam
PH0078	Ø400 mm	19 W	24 V DC	1440 lm	97 CRI	Ø400 x H48 mm; suspension MAX 1900 mm	Ø76 mm	50°
PH0079	Ø600 mm	27 W	24 V DC	2160 lm	97 CRI	Ø600 x H48 mm; suspension MAX 1900 mm	Ø76 mm	50°
PH0080	Ø800 mm	35 W	24 V DC	2880 lm	97 CRI	Ø800 x H48 mm; suspension MAX 1900 mm	Ø76 mm	50°

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for PH0080, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

PH0080, 35 W, 50° beam

