Downlights

# M39 1204 Round

Recessed spotlight




Recessed spotlight. 12 W. Four beam angles, 24° to 60°. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø90 mm
- LED source: Citizen

| Power | Voltage | Colour temperature |
|---|---|---|
| 12 W | 36 V | 2700 K, 3000 K, 4000 K |
| **CRI** | **Beam angles** | **IP rating** |
| 97 CRI | 24°, 36°, 45°, 60° | IP20 |
| **Mounting** | **Control** | **Finishes** |
| Recessed | On/Off | Black |

## Dimensions





## Models


| Code | Version | Power | Voltage | CRI | Size | Cut-out | Beam | Notes |
|---|---|---|---|---|---|---|---|---|
| **RE-M39-1204** | Round | 12 W | 36 V | 97 CRI | Ø97 × 40 mm | Ø90 mm | 24° 36° 45° 60° | 250 mA |

# Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for RE-M39-1204, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.


## RE-M39-1204, 12 W, 24° beam





| | |
|---|---|
| Luminous flux | 900 lm |
| Efficacy | 75 lm/W |
| Peak intensity | 4,575 cd, 5,083 cd/klm |
| Beam angle (50%) | 24° |
| Field angle (10%) | 43.7° |
| Cut-off angle (2.5%) | 27.5° |
| Flux 0–30° / 30–60° / 60–90° | 98.7 / 1.3 / 0 % |
| Size | Ø97 × 40 mm |
| Data | Estimated from catalogue data |


## RE-M39-1204, 12 W, 36° beam





| | |
|---|---|
| Luminous flux | 900 lm |
| Efficacy | 75 lm/W |
| Peak intensity | 2,060 cd, 2,289 cd/klm |
| Beam angle (50%) | 36° |
| Field angle (10%) | 65.6° |
| Cut-off angle (2.5%) | 41.5° |
| Flux 0–30° / 30–60° / 60–90° | 86.1 / 13.9 / 0 % |
| Size | Ø97 × 40 mm |
| Data | Estimated from catalogue data |


## RE-M39-1204, 12 W, 45° beam





| | |
|---|---|
| Luminous flux | 900 lm |
| Efficacy | 75 lm/W |
| Peak intensity | 1,336 cd, 1,485 cd/klm |
| Beam angle (50%) | 45° |
| Field angle (10%) | 82° |
| Cut-off angle (2.5%) | 51.5° |
| Flux 0–30° / 30–60° / 60–90° | 72.2 / 27.2 / 0.6 % |
| Size | Ø97 × 40 mm |
| Data | Estimated from catalogue data |

## RE-M39-1204, 12 W, 60° beam




| | |
|---|---|
| Luminous flux | **900 lm** |
| Efficacy | **75 lm/W** |
| Peak intensity | **774 cd, 860 cd/klm** |
| Beam angle (50%) | **60°** |
| Field angle (10%) | **109.4°** |
| Cut-off angle (2.5%) | **69°** |
| Flux 0–30° / 30–60° / 60–90° | **52.4 / 42.6 / 5 %** |
| Size | **Ø97 × 40 mm** |
| Data | **Estimated from catalogue data** |

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.