

Linear

Robo CH0116

Linear luminaire




Linear luminaire. 15, 30, 45 or 60 W. Four beam angles, 15° to 50°. 2700, 3000, 4000 K. 97 CRI.

— LED source: Citizen

Power 15 W, 30 W, 45 W, 60 W	Voltage 230 V AC	Luminous flux 1300–5200 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°
IP rating IP20	Certifications CE	Mounting Surface
Control DALI	Finishes Black	

Dimensions




Models

Code	Power	Voltage	Flux	CRI	Size	Beam
CH0116	15 W	230 V AC	1300 lm	97 CRI	L250 x W33 x H54 mm, 1 head Ø40 x L150	15° 24° 36° 50°
CH0117	30 W	230 V AC	2600 lm	97 CRI	L400 x W33 x H54 mm, 2 heads Ø40 x L150	15° 24° 36° 50°
CH0118	45 W	230 V AC	3900 lm	97 CRI	L600 x W33 x H54 mm, 3 heads Ø40 x L150	15° 24° 36° 50°
CH0119	60 W	230 V AC	5200 lm	97 CRI	L900 x W33 x H54 mm, 4 heads Ø40 x L150	15° 24° 36° 50°

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for CH0119, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

CH0119, 60 W, 15° beam




Luminous flux	5,200 lm
Efficacy	87 lm/W
Peak intensity	67,234 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø40 × 54 mm
Data	Calculated from catalogue data

CH0119, 60 W, 24° beam




Luminous flux	5,200 lm
Efficacy	87 lm/W
Peak intensity	26,432 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø40 × 54 mm
Data	Calculated from catalogue data

CH0119, 60 W, 36° beam



Luminous flux	5,200 lm
Efficacy	87 lm/W
Peak intensity	11,903 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø40 × 54 mm
Data	Calculated from catalogue data

CH0119, 60 W, 50° beam



Luminous flux	5,200 lm
Efficacy	87 lm/W
Peak intensity	6,308 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0-30° / 30-60° / 60-90°	64.8 / 33.6 / 1.5 %
Size	Ø40 × 54 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.