


Recessed

Robo DL1094

Recessed spotlight



Recessed spotlight. 13 W. Four beam angles, 15° to 50°. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø78 mm
- LED source: Citizen

Power 13 W	Voltage max 37 V	Luminous flux 1200 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°
IP rating IP20	Certifications CE	Mounting Recessed
Finishes White		


Models

Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1094	13 W	max 37 V	1200 lm	97 CRI	86 × 86 x H85 mm; head Ø50 mm	Ø78 mm	15° 24° 36° 50°	350 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1094, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1094, 13 W, 15° beam




Luminous flux	1,200 lm
Efficacy	92 lm/W
Peak intensity	15,516 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	86 × 86 × 85 mm
Data	Calculated from catalogue data

DL1094, 13 W, 24° beam




Luminous flux	1,200 lm
Efficacy	92 lm/W
Peak intensity	6,100 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	86 × 86 × 85 mm
Data	Calculated from catalogue data

DL1094, 13 W, 36° beam



Luminous flux	1,200 lm
Efficacy	92 lm/W
Peak intensity	2,747 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	86 × 86 × 85 mm
Data	Calculated from catalogue data

DL1094, 13 W, 50° beam



Luminous flux	1,200 lm
Efficacy	92 lm/W
Peak intensity	1,456 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0-30° / 30-60° / 60-90°	64.8 / 33.6 / 1.5 %
Size	86 × 86 × 85 mm
Data	Calculated from catalogue data