

Recessed

Robo DL1495

Recessed spotlight




Recessed spotlight. 13 W. Four beam angles, 15° to 50°. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø45 mm
- LED source: Citizen

Power 13 W	Voltage max 37 V	Luminous flux 1170 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°
IP rating IP20	Certifications CE	Mounting Recessed
Finishes Black		

Dimensions




Models

Code	Version	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1495	200 mm stem	13 W	max 37 V	1170 lm	97 CRI	Recessed body Ø60 × 31 mm; stem 200 mm; head Ø40 × 150 mm	Ø45 mm	15° 24° 36° 50°	350 mA
DL1496	400 mm stem	13 W	max 37 V	1170 lm	97 CRI	Recessed body Ø60 × 31 mm; stem 400 mm; head Ø40 × 150 mm	Ø45 mm	15° 24° 36° 50°	350 mA
DL1497	600 mm stem	13 W	max 37 V	1170 lm	97 CRI	Recessed body Ø60 × 31 mm; stem 600 mm; head Ø40 × 150 mm	Ø45 mm	15° 24° 36° 50°	350 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1495, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1495, 13 W, 15° beam




Luminous flux	1,170 lm
Efficacy	90 lm/W
Peak intensity	15,128 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø60 × 31 mm
Data	Calculated from catalogue data

DL1495, 13 W, 24° beam




Luminous flux	1,170 lm
Efficacy	90 lm/W
Peak intensity	5,947 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø60 × 31 mm
Data	Calculated from catalogue data

DL1495, 13 W, 36° beam



Luminous flux	1,170 lm
Efficacy	90 lm/W
Peak intensity	2,678 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø60 × 31 mm
Data	Calculated from catalogue data

DL1495, 13 W, 50° beam



Luminous flux	1,170 lm
Efficacy	90 lm/W
Peak intensity	1,419 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0-30° / 30-60° / 60-90°	64.8 / 33.6 / 1.5 %
Size	Ø60 × 31 mm
Data	Calculated from catalogue data