

Recessed

Robo DL1811

Recessed spotlight




Recessed spotlight. 2 or 4 W. Four beam angles, 15° to 60°. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø45 / Ø68 mm
- LED source: Citizen

Power 2 W, 4 W	Voltage max 6 V, max 3 V	Luminous flux 2 × 140 lm, 140 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 60°
IP rating IP20	Certifications CE	Mounting Recessed
Finishes White		

Dimensions




Models

Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1811	4 W	max 6 V	2 × 140 lm	97 CRI	$\varnothing 60 \times 54$ (flange height 9 mm)	$\varnothing 45$ mm	15° 24° 36° 60°	700 mA
DL1810	2 W	max 3 V	140 lm	97 CRI	$\varnothing 34$ housing, plaster flange 80 × 37, heights 48 / 14 / 18 mm	$\varnothing 45$ mm	15° 24° 36° 60°	700 mA
DL1812	4 W	max 6 V	2 × 140 lm	97 CRI	$\varnothing 55$ housing, plaster flange 112 × 64, heights 54 / 9 / 46 mm	$\varnothing 68$ mm	15° 24° 36° 60°	700 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1811, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1811, 4 W, 15° beam




Luminous flux	280 lm
Efficacy	70 lm/W
Peak intensity	3,620 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø60 × 54 mm
Data	Calculated from catalogue data

DL1811, 4 W, 24° beam




Luminous flux	280 lm
Efficacy	70 lm/W
Peak intensity	1,423 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø60 × 54 mm
Data	Calculated from catalogue data

DL1811, 4 W, 36° beam



Luminous flux	280 lm
Efficacy	70 lm/W
Peak intensity	641 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø60 × 54 mm
Data	Calculated from catalogue data

DL1811, 4 W, 60° beam



Luminous flux	280 lm
Efficacy	70 lm/W
Peak intensity	241 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Size	Ø60 × 54 mm
Data	Calculated from catalogue data