

Track spotlights

S3-4045N

Track spotlight




Track spotlight. 28 W. Five beam angles, 10° to 50°. 3000, 4000 K. 97 CRI.

— LED source: Citizen

Power 28 W	Voltage 220–240 V AC	Luminous flux 2600–2800 lm
Colour temperature 3000 K, 4000 K	CRI 97 CRI	Beam angles 10°, 15°, 24°, 36°, 50°
IP rating IP20	Certifications CE, RoHS, EMC, LVD	Mounting Magnetic track
Control On/Off, DALI, 0-10V, Triac, Casambi	Finishes White, Black, Grey	

Dimensions




Models

Code	Version	Power	Voltage	Flux	CRI	Size	Beam
S3-4045N	160 × 38 adapter	28 W	220–240 V AC	2600–2800 lm	97 CRI	Ø73 × 140 mm	10° 15° 24° 36° 50°

Photometric data

Illuminance on the beam axis (lx) and beam diameter at each mounting distance, per model and beam angle. IES files for every model and beam can be downloaded from the product page.


28 W



Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for S3-4045N, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

S3-4045N, 28 W, 15° beam




Luminous flux	832 lm
Efficacy	30 lm/W
Peak intensity	10,760 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø73 × 140 mm
Data	Calculated from catalogue data

S3-4045N, 28 W, 24° beam




Luminous flux	1,597 lm
Efficacy	57 lm/W
Peak intensity	8,120 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø73 × 140 mm
Data	Calculated from catalogue data

S3-4045N, 28 W, 36° beam




Luminous flux	2,027 lm
Efficacy	72 lm/W
Peak intensity	4,640 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø73 × 140 mm
Data	Calculated from catalogue data

S3-4045N, 28 W, 10° beam



Luminous flux	2,600 lm
Efficacy	93 lm/W
Peak intensity	75,466 cd, 29,025 cd/klm
Beam angle (50%)	10°
Field angle (10%)	18.2°
Cut-off angle (2.5%)	11.5°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø73 × 140 mm
Data	Calculated from catalogue data

S3-4045N, 28 W, 50° beam



Luminous flux	2,600 lm
Efficacy	93 lm/W
Peak intensity	3,154 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0–30° / 30–60° / 60–90°	64.8 / 33.6 / 1.5 %
Size	Ø73 × 140 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.