Track spotlights

S3-6003

Track spotlight

Track spotlight. 28 W. Four beam angles, 15° to 55°. 3000, 4000 K. 97 CRI.

- LED source: Citizen

Power **28 W**	Voltage **220–240 V AC**	Luminous flux **2600–2900 lm**
Colour temperature **3000 K, 4000 K**	CRI **97 CRI**	Beam angles **15°, 24°, 45°, 55°**
IP rating **IP20**	Certifications **CE, RoHS, EMC, LVD**	Mounting **Magnetic track**
Control **On/Off, DALI, 0-10V, Triac, Casambi**	Finishes **White, Black, Grey**	

Dimensions



Models

Code	Power	Voltage	Flux	CRI	Size	Beam
S3-6003	28 W	220–240 V AC	2600–2900 lm	97 CRI	Ø85 × 105 mm	15° 24° 45° 55°

Photometric data

Illuminance on the beam axis (lx) and beam diameter at each mounting distance, per model and beam angle. IES files for every model and beam can be downloaded from the product page.

28 W



Beam	1 m	2 m	3 m
15°	12,998 lx Ø330 mm	3,249 lx Ø660 mm	1,444 lx Ø1000 mm
30°	6,686 lx Ø520 mm	1,671 lx Ø1030 mm	742 lx Ø1550 mm
45°	4,957 lx Ø700 mm	1,239 lx Ø1400 mm	550 lx Ø2100 mm

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for S3-6003, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

S3-6003, 28 W, 15° beam





Luminous flux	1,005 lm
Efficacy	36 lm/W
Peak intensity	12,996 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø85 × 105 mm
Data	Calculated from catalogue data

S3-6003, 28 W, 30° beam





Luminous flux	2,042 lm
Efficacy	73 lm/W
Peak intensity	6,684 cd, 3,273 cd/klm
Beam angle (50%)	30°
Field angle (10%)	54.7°
Cut-off angle (2.5%)	34.5°
Flux 0–30° / 30–60° / 60–90°	94 / 6 / 0 %
Size	Ø85 × 105 mm
Data	Calculated from catalogue data

S3-6003, 28 W, 45° beam





Luminous flux	3,338 lm
Efficacy	119 lm/W
Peak intensity	4,956 cd, 1,485 cd/klm
Beam angle (50%)	45°
Field angle (10%)	82°
Cut-off angle (2.5%)	51.5°
Flux 0–30° / 30–60° / 60–90°	72.2 / 27.2 / 0.6 %
Size	Ø85 × 105 mm
Data	Calculated from catalogue data

S3-6003, 28 W, 24° beam





Luminous flux	2,600 lm
Efficacy	93 lm/W
Peak intensity	13,216 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø85 × 105 mm
Data	Calculated from catalogue data

S3-6003, 28 W, 55° beam





Luminous flux	2,600 lm
Efficacy	93 lm/W
Peak intensity	2,632 cd, 1,012 cd/klm
Beam angle (50%)	55°
Field angle (10%)	100.2°
Cut-off angle (2.5%)	63°
Flux 0–30° / 30–60° / 60–90°	58.2 / 38.8 / 3 %
Size	Ø85 × 105 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.