Chandel-Track 13 mm system

SM06-DF200

Chandel-Track linear luminaire




Linear luminaire for the Chandel-Track 48 V track system. 5 W. 105° beam. 2700, 3000, 4000, 5000 K. 97 CRI.

- LED source: Citizen

Power	Voltage	Colour temperature
5 W	48 V DC	2700 K, 3000 K, 4000 K, 5000 K
CRI	**Beam angles**	**Mounting**
97 CRI	105°	Magnetic track
Finishes		
Black		

Dimensions




Models


Code	Power	Voltage	CRI	Size	Beam
SM06-DF200	5 W	48 V DC	97 CRI	233 × 7 × 8 mm	105°

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for SM06-DF200, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

SM06-DF200, 5 W, 105° beam





Luminous flux	300 lm
Efficacy	60 lm/W
Peak intensity	104 cd, 348 cd/klm
Beam angle (50%)	105°
Cut-off angle (2.5%)	90°
Flux 0–30° / 30–60° / 60–90°	26.2 / 46.7 / 27.1 %
Size	233 × 7 × 8 mm
Data	Estimated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.