Chandel-Track 13 mm system

SM06-DF300

Chandel-Track linear luminaire




Linear luminaire for the Chandel-Track 48 V track system. 7 W. 105° beam. 2700, 3000, 4000, 5000 K. 97 CRI.

- LED source: Citizen

Power	Voltage	Colour temperature
7 W	48 V DC	2700 K, 3000 K, 4000 K, 5000 K
CRI	**Beam angles**	**Mounting**
97 CRI	105°	Magnetic track
Finishes		
Black		

Dimensions




Models


Code	Power	Voltage	CRI	Size	Beam
SM06-DF300	7 W	48 V DC	97 CRI	333 × 7 × 8 mm	105°

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for SM06-DF300, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

SM06-DF300, 7 W, 105° beam





Luminous flux	**420 lm**
Efficacy	**60 lm/W**
Peak intensity	**146 cd, 348 cd/klm**
Beam angle (50%)	**105°**
Cut-off angle (2.5%)	**90°**
Flux 0–30° / 30–60° / 60–90°	**26.2 / 46.7 / 27.1 %**
Size	**333 × 7 × 8 mm**
Data	**Estimated from catalogue data**

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.