Wall

Star DL1146

Wall light



Wall light.

- Ceiling cut-out Ø32 mm
- LED source: Citizen

Voltage **max 3 V**	Luminous flux **20 / 40 lm**	Colour temperature **2700 K, 3000 K, 4000 K**
CRI **97 CRI**	IP rating **IP20**	Certifications **CE**
Mounting **Recessed, Wall**	Finishes **White**	

Models

Code	Voltage	Flux	CRI	Size	Cut-out	Notes
DL1146	max 3 V	20 / 40 lm	97 CRI	92 × 35 × 25 mm	Ø32 mm	350 / 700 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1146, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1146, wide distribution





Luminous flux	20 lm
Peak intensity	6 cd, 318 cd/klm
Beam angle (50%)	120°
Field angle (10%)	168.5°
Cut-off angle (2.5%)	88.5°
Flux 0–30° / 30–60° / 60–90°	25 / 50 / 25 %
Size	92 × 35 × 25 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.