Surface

SU-M6-1501

Surface luminaire



Surface luminaire. 15 W. Four beam angles, 15° to 50°. 2700, 3000, 4000, 5000 K. 97 CRI.

- LED source: Citizen

Power **15 W**	Voltage **36 V**	Colour temperature **2700 K, 3000 K, 4000 K, 5000 K**
CRI **97 CRI**	Beam angles **15°, 24°, 36°, 50°**	IP rating **IP20**
Mounting **Surface**	Control **On/Off, Triac**	Finishes **Black**

Dimensions



Models

Code	Power	Voltage	CRI	Size	Beam	Notes
SU-M6-1501	15 W	36 V	97 CRI	265 × 30 mm	15° 24° 36° 50°	350 mA

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for SU-M6-1501, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

SU-M6-1501, 15 W, 15° beam





Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	14,546 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	265 × 30 mm
Data	Estimated from catalogue data

SU-M6-1501, 15 W, 24° beam





Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	5,719 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	265 × 30 mm
Data	Estimated from catalogue data

SU-M6-1501, 15 W, 36° beam





Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	2,575 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	265 × 30 mm
Data	Estimated from catalogue data

SU-M6-1501, 15 W, 50° beam





Luminous flux	1,125 lm
Efficacy	75 lm/W
Peak intensity	1,365 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0–30° / 30–60° / 60–90°	64.8 / 33.6 / 1.5 %
Size	265 × 30 mm
Data	Estimated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.