


Floor

TA-01-8W-200

Floor lamp




Floor lamp. 8 W. Four beam angles, 15° to 50°. 2700, 3000, 4000, 5000 K. 97 CRI.

— LED source: Citizen

Power 8 W	Voltage 18 V	Colour temperature 2700 K, 3000 K, 4000 K, 5000 K
CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°	IP rating IP20
Mounting Floor	Finishes Black	

Dimensions




Models

Code	Power	Voltage	CRI	Size	Beam	Notes
TA-01-8W-200	8 W	18 V	97 CRI	Ø48 × 120 mm head, 200 mm high, base Ø55 mm	15° 24° 36° 50°	400 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for TA-01-8W-200, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

TA-01-8W-200, 8 W, 15° beam




Luminous flux	600 lm
Efficacy	75 lm/W
Peak intensity	7,758 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø48 × 120 mm
Data	Estimated from catalogue data

TA-01-8W-200, 8 W, 24° beam




Luminous flux	600 lm
Efficacy	75 lm/W
Peak intensity	3,050 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø48 × 120 mm
Data	Estimated from catalogue data

TA-01-8W-200, 8 W, 36° beam



Luminous flux	600 lm
Efficacy	75 lm/W
Peak intensity	1,373 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø48 × 120 mm
Data	Estimated from catalogue data

TA-01-8W-200, 8 W, 50° beam



Luminous flux	600 lm
Efficacy	75 lm/W
Peak intensity	728 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0–30° / 30–60° / 60–90°	64.8 / 33.6 / 1.5 %
Size	Ø48 × 120 mm
Data	Estimated from catalogue data