Linear

Tour Forty8 TR0277

Linear track luminaire

Linear track luminaire. 5 W. 2700, 3000, 4000 K. 97 CRI.

- LED source: Citizen

Power **5 W**	Voltage **48 V DC**	Luminous flux **400 lm**
Colour temperature **2700 K, 3000 K, 4000 K**	CRI **97 CRI**	IP rating **IP20**
Certifications **CE**	Mounting **Magnetic track**	Finishes **Black**

Models

Code	Power	Voltage	Flux	CRI	Size
TR0277	5 W	48 V DC	400 lm	97 CRI	Ø100 × 38 mm

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for TR0277, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

TR0277, 5 W, wide distribution





Luminous flux	400 lm
Efficacy	80 lm/W
Peak intensity	127 cd, 318 cd/klm
Beam angle (50%)	120°
Field angle (10%)	168.5°
Cut-off angle (2.5%)	88.5°
Flux 0–30° / 30–60° / 60–90°	25 / 50 / 25 %
Size	Ø100 × 38 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.