

Track spotlights

Tour Forty8 TR0288

Track spotlight



Track spotlight. 3 W. Four beam angles, 15° to 60°. 2700, 3000, 4000 K. 97 CRI.

— LED source: Citizen

Power 3 W	Voltage 48 V DC	Luminous flux 240 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 60°
IP rating IP20	Certifications CE	Mounting Magnetic track
Finishes Black		


Models

Code	Power	Voltage	Flux	CRI	Size	Beam
TR0288	3 W	48 V DC	240 lm	97 CRI	Ø20 × 70 mm	15° 24° 36° 60°

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for TR0288, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

TR0288, 3 W, 15° beam




Luminous flux	240 lm
Efficacy	80 lm/W
Peak intensity	3,103 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø20 × 70 mm
Data	Calculated from catalogue data

TR0288, 3 W, 24° beam




Luminous flux	240 lm
Efficacy	80 lm/W
Peak intensity	1,220 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø20 × 70 mm
Data	Calculated from catalogue data

TR0288, 3 W, 36° beam



Luminous flux	240 lm
Efficacy	80 lm/W
Peak intensity	549 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø20 × 70 mm
Data	Calculated from catalogue data

TR0288, 3 W, 60° beam



Luminous flux	240 lm
Efficacy	80 lm/W
Peak intensity	206 cd, 860 cd/klm
Beam angle (50%)	60°
Field angle (10%)	109.4°
Cut-off angle (2.5%)	69°
Flux 0–30° / 30–60° / 60–90°	52.4 / 42.6 / 5 %
Size	Ø20 × 70 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.