Suspended

Tour Forty8 TR0298

Pendant

Pendant. 7 W. Four beam angles, 15° to 55°. 2700, 3000, 4000 K. 97 CRI.

- LED source: Citizen

Power **7 W**	Voltage **48 V DC**	Luminous flux **560 lm**
Colour temperature **2700 K, 3000 K, 4000 K**	CRI **97 CRI**	Beam angles **15°, 24°, 36°, 55°**
IP rating **IP20**	Certifications **CE**	Mounting **Suspended, Magnetic track**
Finishes **Black**		

Models

Code	Power	Voltage	Flux	CRI	Size	Beam
TR0298	7 W	48 V DC	560 lm	97 CRI	Ø78 × 91 mm	15° 24° 36° 55°

Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for TR0298, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

TR0298, 7 W, 15° beam





Luminous flux	560 lm
Efficacy	80 lm/W
Peak intensity	7,241 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø78 × 91 mm
Data	Calculated from catalogue data

TR0298, 7 W, 24° beam





Luminous flux	560 lm
Efficacy	80 lm/W
Peak intensity	2,847 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø78 × 91 mm
Data	Calculated from catalogue data

TR0298, 7 W, 36° beam





Luminous flux	560 lm
Efficacy	80 lm/W
Peak intensity	1,282 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø78 × 91 mm
Data	Calculated from catalogue data

TR0298, 7 W, 55° beam





Luminous flux	560 lm
Efficacy	80 lm/W
Peak intensity	567 cd, 1,012 cd/klm
Beam angle (50%)	55°
Field angle (10%)	100.2°
Cut-off angle (2.5%)	63°
Flux 0–30° / 30–60° / 60–90°	58.2 / 38.8 / 3 %
Size	Ø78 × 91 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.