Track spotlights

# Tour TR0141

Track spotlight

Track spotlight. 15 W. Four beam angles, 15° to 50°. 2700, 3000, 4000 K. 97 CRI.

- LED source: Citizen

| | | |
|---|---|---|
| Power<br>**15 W** | Voltage<br>**48 V DC** | Luminous flux<br>**1300 lm** |
| Colour temperature<br>**2700 K, 3000 K, 4000 K** | CRI<br>**97 CRI** | Beam angles<br>**15°, 24°, 36°, 50°** |
| IP rating<br>**IP20** | Certifications<br>**CE, Class III** | Mounting<br>**Magnetic track** |
| Finishes<br>**Black** | | |

## Dimensions




## Models

| Code | Power | Voltage | Flux | CRI | Size | Beam |
|---|---|---|---|---|---|---|
| **TR0141** | 15 W | 48 V DC | 1300 lm | 97 CRI | Ø50 × 150 mm | 15° 24° 36° 50° |

# Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for TR0141, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

## TR0141, 15 W, 15° beam







| | |
|---|---|
| Luminous flux | 1,300 lm |
| Efficacy | 87 lm/W |
| Peak intensity | 16,809 cd, 12,930 cd/klm |
| Beam angle (50%) | 15° |
| Field angle (10%) | 27.3° |
| Cut-off angle (2.5%) | 17° |
| Flux 0–30° / 30–60° / 60–90° | 100 / 0 / 0 % |
| Size | Ø50 × 150 mm |
| Data | Calculated from catalogue data |

## TR0141, 15 W, 24° beam







| | |
|---|---|
| Luminous flux | 1,300 lm |
| Efficacy | 87 lm/W |
| Peak intensity | 6,608 cd, 5,083 cd/klm |
| Beam angle (50%) | 24° |
| Field angle (10%) | 43.7° |
| Cut-off angle (2.5%) | 27.5° |
| Flux 0–30° / 30–60° / 60–90° | 98.7 / 1.3 / 0 % |
| Size | Ø50 × 150 mm |
| Data | Calculated from catalogue data |

## TR0141, 15 W, 36° beam







| | |
|---|---|
| Luminous flux | 1,300 lm |
| Efficacy | 87 lm/W |
| Peak intensity | 2,976 cd, 2,289 cd/klm |
| Beam angle (50%) | 36° |
| Field angle (10%) | 65.6° |
| Cut-off angle (2.5%) | 41.5° |
| Flux 0–30° / 30–60° / 60–90° | 86.1 / 13.9 / 0 % |
| Size | Ø50 × 150 mm |
| Data | Calculated from catalogue data |

## TR0141, 15 W, 50° beam







| | |
|---|---|
| Luminous flux | 1,300 lm |
| Efficacy | 87 lm/W |
| Peak intensity | 1,577 cd, 1,213 cd/klm |
| Beam angle (50%) | 50° |
| Field angle (10%) | 91.1° |
| Cut-off angle (2.5%) | 57.5° |
| Flux 0–30° / 30–60° / 60–90° | 64.8 / 33.6 / 1.5 % |
| Size | Ø50 × 150 mm |
| Data | Calculated from catalogue data |

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.