

Recessed

Vero DL1411

Recessed spotlight



Recessed spotlight. 7 or 10 W. Four beam angles, 15° to 50°. 2700, 3000, 4000 K. IP54. 97 CRI.

- Ceiling cut-out Ø70 mm
- LED source: Citizen

Power 7 W, 10 W	Voltage max 19 V	Luminous flux 630 lm, 960 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°
IP rating IP54	Certifications CE	Mounting Recessed
Finishes White		


Models

Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1411	7 W	max 19 V	630 lm	97 CRI	Ø80 x H89 mm	Ø70 mm	15° 24° 36° 50°	350 mA
DL1411	10 W	max 19 V	960 lm	97 CRI	Ø80 x H89 mm	Ø70 mm	15° 24° 36° 50°	500 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1411, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1411, 10 W, 15° beam




Luminous flux	960 lm
Efficacy	96 lm/W
Peak intensity	12,412 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø80 × 89 mm
Data	Calculated from catalogue data

DL1411, 10 W, 24° beam





Luminous flux	960 lm
Efficacy	96 lm/W
Peak intensity	4,880 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø80 × 89 mm
Data	Calculated from catalogue data

DL1411, 10 W, 36° beam



Luminous flux	960 lm
Efficacy	96 lm/W
Peak intensity	2,198 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø80 × 89 mm
Data	Calculated from catalogue data

DL1411, 10 W, 50° beam



Luminous flux	960 lm
Efficacy	96 lm/W
Peak intensity	1,164 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0–30° / 30–60° / 60–90°	64.8 / 33.6 / 1.5 %
Size	Ø80 × 89 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.