

Recessed

Vero DL1438

Recessed spotlight




Recessed spotlight. 7 or 10 W. Four beam angles, 15° to 50°. 2700, 3000, 4000 K. 97 CRI.

- Ceiling cut-out Ø68 mm
- LED source: Citizen

Power 7 W, 10 W	Voltage max 19 V	Luminous flux 560 lm, 780 lm
Colour temperature 2700 K, 3000 K, 4000 K	CRI 97 CRI	Beam angles 15°, 24°, 36°, 50°
IP rating IP20	Certifications CE	Mounting Recessed
Finishes White		

Dimensions




Models

Code	Power	Voltage	Flux	CRI	Size	Cut-out	Beam	Notes
DL1438	7 W	max 19 V	560 lm	97 CRI	Ø55 × 74 mm (plates 113 × 64)	Ø68 mm	15° 24° 36° 50°	350 / 500 mA
DL1438	10 W	max 19 V	780 lm	97 CRI	Ø55 × 74 mm (plates 113 × 64)	Ø68 mm	15° 24° 36° 50°	350 / 500 mA

Photometry


Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for DL1438, from the same data as the IES and LDT files on the product page. Calculated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.

DL1438, 10 W, 15° beam




Luminous flux	780 lm
Efficacy	78 lm/W
Peak intensity	10,085 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø55 × 74 mm
Data	Calculated from catalogue data

DL1438, 10 W, 24° beam





Luminous flux	780 lm
Efficacy	78 lm/W
Peak intensity	3,965 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø55 × 74 mm
Data	Calculated from catalogue data

DL1438, 10 W, 36° beam



Luminous flux	780 lm
Efficacy	78 lm/W
Peak intensity	1,785 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø55 × 74 mm
Data	Calculated from catalogue data

DL1438, 10 W, 50° beam



Luminous flux	780 lm
Efficacy	78 lm/W
Peak intensity	946 cd, 1,213 cd/klm
Beam angle (50%)	50°
Field angle (10%)	91.1°
Cut-off angle (2.5%)	57.5°
Flux 0–30° / 30–60° / 60–90°	64.8 / 33.6 / 1.5 %
Size	Ø55 × 74 mm
Data	Calculated from catalogue data

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.