Outdoor

M26 0603

Outdoor luminaire




Outdoor luminaire. 6 W. Four beam angles, 15° to 50°. 2700, 3000, 4000 K. IP65. 97 CRI.

- LED source: Citizen

Power	Voltage	Colour temperature
6 W	220–240 V AC	2700 K, 3000 K, 4000 K
CRI	**Beam angles**	**IP rating**
97 CRI	15°, 24°, 36°, 50°	IP65
Mounting	**Control**	**Finishes**
Wall	On/Off	White, Black, Silver, Brass, Bronze

Dimensions



Models

Code	Power	Voltage	CRI	Size	Beam	Notes
WA-M26-0603	6 W	220–240 V AC	97 CRI	Ø43 × 175.5 mm, depth 65.8 mm	15° 24° 36° 50°	150 mA


Finishes




Photometry

Polar curve, on-axis illuminance with beam diameter at 1–5 m, and key figures for WA-M26-0603, from the same data as the IES and LDT files on the product page. Estimated from catalogue data, not measured with a goniophotometer. Other models with the same beam share this distribution, scaled to their luminous flux.


WA-M26-0603, 6 W, 15° beam






Luminous flux	450 lm
Efficacy	75 lm/W
Peak intensity	5,818 cd, 12,930 cd/klm
Beam angle (50%)	15°
Field angle (10%)	27.3°
Cut-off angle (2.5%)	17°
Flux 0–30° / 30–60° / 60–90°	100 / 0 / 0 %
Size	Ø43 × 175.5 mm
Data	Estimated from catalogue data


WA-M26-0603, 6 W, 24° beam






Luminous flux	450 lm
Efficacy	75 lm/W
Peak intensity	2,287 cd, 5,083 cd/klm
Beam angle (50%)	24°
Field angle (10%)	43.7°
Cut-off angle (2.5%)	27.5°
Flux 0–30° / 30–60° / 60–90°	98.7 / 1.3 / 0 %
Size	Ø43 × 175.5 mm
Data	Estimated from catalogue data


WA-M26-0603, 6 W, 36° beam






Luminous flux	450 lm
Efficacy	75 lm/W
Peak intensity	1,030 cd, 2,289 cd/klm
Beam angle (50%)	36°
Field angle (10%)	65.6°
Cut-off angle (2.5%)	41.5°
Flux 0–30° / 30–60° / 60–90°	86.1 / 13.9 / 0 %
Size	Ø43 × 175.5 mm
Data	Estimated from catalogue data

WA-M26-0603, 6 W, 50° beam





Luminous flux	**450 lm**
Efficacy	**75 lm/W**
Peak intensity	**546 cd, 1,213 cd/klm**
Beam angle (50%)	**50°**
Field angle (10%)	**91.1°**
Cut-off angle (2.5%)	**57.5°**
Flux 0–30° / 30–60° / 60–90°	**64.8 / 33.6 / 1.5 %**
Size	**Ø43 × 175.5 mm**
Data	**Estimated from catalogue data**

DiaNoche
service@dianoche.it
dianoche.it

Technical data may change without notice.